

ARCHOIL AR6350 COLD WEATHER PROTECT

ANTI WAX FOR DIESEL & BIO FUELS

AR6350 is a concentrated cold flow technology designed to protect against waxing and plugging of fuel filters. AR6350 has been tested extensively to improve the CFPP (Cold Filter Pugging Point) of diesel and gas oils.

AR6350 is suitable for all pump diesel fuels and some bio-diesel blends. As fuels vary considerably it is recommend that the CFPP for your particular fuel is tested to achieve the desired level of protection.

FEATURES / BENEFITS:

- 🔥 Considerably lowers CFPP
- 🔥 Inhibits the formation of wax crystals
- 🔥 Compatible with maximum permitted FAME contents
- 🔥 Enables fuel to be safely used in lower temperature conditions
- 🔥 Concentrated formula so less product required

INSTRUCTIONS:

AR6350 will not correct existing wax formation and must be used as a preventative only. The fuel being treated must be at a minimum of 5°C or product efficacy may be reduced.

Add AR6350 at a ratio of 1,000:1 and mildly agitate the fuel.

| | CFPP Standard | CFPP + AR6350 Ratio 1000:1 |
|------------------------|---------------|----------------------------|
| BS EN590 Summer Diesel | 5 | -20 estimated |
| BS EN590 Winter Diesel | -15 | -26 estimated |
| A2 Gas Oil Summer | -4 | -19 estimated |
| A2 Gas Oil Winter | -12 | -25 estimated |

Please note: results may vary.

PACKAGING:

250ml, 1 litre, 5 litre, 20 litre and 200 litre Drum.

AR6350 Cold Weather Protect

